Inventory for August 5th

Make sure to email Launch 3 at sales@launch3.net or call at 877-878-9134 to acquire the following inventory:

Manufacturer	Part Number	Description
123eWireless	MP155HA128	Category 5E Patch Panel, 12 Port, RJ45-110
Alcatel-Lucent	486AA	ALCATEL-LUCENT 5ESS DC TO DC CONV
Alcatel-Lucent	410CA	POWER UNIT SER 18
Andrew	L4A-PDRDM-30-USX	LDF4-50A SureFlex 30FT Jumper with interface types 7-16 DIN
ARGUS	012-526-20-040	CONVERTER MODULES 37A, MAX OF 4 PER SHELF, 24-48
Burndy	YA6CL4	BURNDY; Compression Terminal; HYLUG; YA-L, Code Conduc Holes: 1; Material: Copper; Voltage Rating: 600 - 35000 V; Tong IN; Package: Box; Finish: Electro-Tin Plated; Die Index: 7; Color Mechanical: MD6, OUR840, MD7-34R Tool, W5CVT, W5CRT, X W5CRT, X5CRT, X8CART Die, (1); Y35, Y39, Y750, PAT750 To PUADP-1 Adapter, (1); Conductor Type: Commercial Stranded C Y1MRTC, PAT81KFT-18V, MY29-3, MY29-11, MRC840 Tool, (1
Burndy	T14-6	Uninsulated Compression Terminal,Ring Tongue; 4-6; 0.67 in L;
Cantex	5233829	Cantex SCH 40 90 Degree elbow is manufactured from heat trea in a conduit run. Gray colored elbow features solvent weld ends connection elbow features a trade size of 2 1/2 Inch, radius of 36 2.875 Inch outer diameter. Elbow meets ETL list, UL651, NEMA
Cantex	5233832	SCH 40 90 Degree Elbow; 4 Inch, Belled, 25.125 Inch Length, R
Cantex	5233832	SCH 40 90 Degree Elbow; 4 Inch, Belled, 25.125 Inch Length, R
Cantex	5233825	SCH 40 90 Degree Elbow; 1 Inch, Belled, Rigid PVC
Cantex	5233765	45 Degree Bell End Elbow with Standard Radius; 1 In
Cantex	5233764	SCH 40 45 Degree Elbow; 3/4 Inch, Belled, Rigid PVC
Cantex	5233825	SCH 40 90 Degree Elbow; 1 Inch, Belled, Rigid PVC
Cantex	5140048	Cantex Adapter in gray color is made of rigid PVC for corrosion r threaded and the other is solvent weld. The SCH 40/80 measure transition of threaded metal conduit to PVC conduit. Adapter is U
Carlon	UA7AJ-CAR	SCH 40 45 Degree Rigid Non-Metallic Elbow; 2 Inch, Plain End,
Ceragon	PORAM-11-NW	04-0228-1 11Ghz remote antenna mount REV A.00
Cooper B-Line	BOX 312J	COOPER B-LINE J & P BOX 312J SC w/ 3 Baco Switches 23E0
ECI	79793210501	T:Dax PE1 Intfc
Ericsson	KRY1011884/1	KRY1011884/1 R2B TMA Bias Injector Kit with (2) KRY 101158
Littelfuse	LB7	Conduit Bodies, LB Rigid Threaded Type, Copper Free Aluminu
Magnetek	A011989	Small Access Power System APS48-1G7MA1.5LA Rev B
NEWTON	40860000	23 INSULATOR FOR FREESTANDING RACK
Powerstrut	PS 1100	Standard Pipe Clamp (GRC, IMC and SCH 40, SCH 80 steel pip
RFS	FD9R6004/1C-3L	ShareLite Wideband Diplexer â€“ In-line 698-960 MHz/1710-220 designed to enable feeder sharing between systems in the 698-9 AWS-3 paired spectrum blocks (G, H, I, J).. The diplexer is equip

		cabinet or at the tower top. This is especially valuable in crowde design, the FD9R6004 Series can accommodate many combinir LTE 700 MHz, Cellular 800 MHz with PCS, GSM900 with GSM1 provides a high level of isolation between ports, while keeping th diplexers are available with various DC pass options, helpful in c
Riverstone	G86-PDC	INSIDE CHASIS G86-CHS RS8600
Riverstone	G8M-P12B1-02	POS OC-12C MMF
Thomas & Betts	SRPE-375-9-C	SPIRAL WRAP, PE, NATURAL, 0.375IN OD, 100FT
Topaz	LB7	Conduit Bodies, LB Rigid Threaded Type, Copper Free Aluminu